

ELECTRIC CHARACTERISTICS

Nominal voltage	400 Vac (480 Vac or additional voltage available upon request)
Frequency	50/60 Hz
Regulation	Independent
Core type	Toroidal
Input	Symmetric

FINSTTY	Rated Power (KVA)	Rated Current (A)	Voltage Variation (%)	Response Time (ms/V)	Output Accuracy ($\pm\%$)	Dimensions (mm) a x b x h	Weight Kg	Case
FINSTTY.30.A3	3	4	± 30	13	± 1	650X450X1000	90	3
FINSTTY.25.A4.5	4.5	7	± 25	14	± 1	650X450X1000	90	3
FINSTTY.20.A6	6	9	± 20	16	± 1	650X450X1000	90	3
FINSTTY.15.A7.5	7.5	11	± 15	18	± 1	650X450X1000	90	3
FINSTTY.10.A10	10	14	± 10	21	± 1	650X450X1000	90	3
FINSTTY.30.B6	6	9	± 30	11	± 1	650X450X1000	115	3
FINSTTY.25.B9	9	13	± 25	12	± 1	650X450X1000	115	3
FINSTTY.20.B12	12	17	± 20	14	± 1	650X450X1000	115	3
FINSTTY.15.B15	15	22	± 15	16	± 1	650X450X1000	115	3
FINSTTY.10.B24	24	35	± 10	19	± 1	650X450X1000	115	3
FINSTTY.30.C9	9	13	± 30	13	± 1	650X450X1000	135	3
FINSTTY.25.C15	15	22	± 25	14	± 1	650X450X1000	135	3
FINSTTY.20.C18	18	26	± 20	16	± 1	650X450X1000	135	3
FINSTTY.15.C21	21	30	± 15	18	± 1	650X450X1000	135	3
FINSTTY.10.C30	30	43	± 10	21	± 1	650X450X1000	135	3
FINSTTY.30.D18	18	26	± 30	13	± 1	650X450X1000	210	3
FINSTTY.25.D24	24	35	± 25	14	± 1	650X450X1000	210	3
FINSTTY.20.D30	30	43	± 20	16	± 1	650X450X1000	210	3
FINSTTY.15.D45	45	65	± 15	18	± 1	650X450X1000	210	3
FINSTTY.10.D60	60	87	± 10	21	± 1	650X450X1000	210	3
FINSTTY.30.E30	30	43	± 30	13	± 1	650X450X1300	240	3
FINSTTY.25.E36	36	52	± 25	14	± 1	650X450X1300	240	3
FINSTTY.20.E46	46	66	± 20	16	± 1	650X450X1300	240	3
FINSTTY.15.E66	66	95	± 15	18	± 1	650X450X1300	240	3
FINSTTY.10.E105	105	152	± 10	21	± 1	650X450X1300	240	3
FINSTTY.30.F36	36	43	± 15	13	± 1	650X450X1300	290	3
FINSTTY.25.F45	45	52	± 15	14	± 1	650X450X1300	290	3
FINSTTY.20.F60	60	66	± 15	16	± 1	650X450X1300	290	3
FINSTTY.15.F90	90	95	± 15	18	± 1	650X450X1300	290	3
FINSTTY.10.F120	120	152	± 15	21	± 1	650X450X1300	290	3

CASE 3
